

Safety Data Sheet

Formula No: 2104

Revision Date: 2017/10/24 Superseded Date: 2015/05/01

Mirachem Ultrasonic XL

1. IDENTIFICATION OF SUBSTANCE / PREPARATION AND OF THE COMPANY

Product name: Mirachem Ultrasonic XL

Identified uses: Concentrated industrial cleaner for use in industrial ultrasonic parts washers.

Use restrictions: Use only for the purposes indicated on the label.

Company: Mirachem, LLC

P.O. Box 14059

Phoenix, Arizona 85063-4059

USA

Email address: <u>SDS@mirachem.com</u>

Customer service: USA (English) Telephone: 1 (800) 847-3527

Emergency phone number(s): USA (English, Business Hours) Telephone: 1 (800) 847-3527

Chemtrec (US, 24 hours) Telephone: 1 (800) 424-9300

2. HAZARD(S) IDENTIFICATION

GHS ClassificationSKIN CORROSION/IRRITATION:Category 2EYE DAMAGE/IRRITATION:Category 2AACUTE AQUATIC HAZARD:Category 2

GHS Label Elements
Pictogram

Signal word

Hazard statements Causes skin irritation. (H315)

Warning

Causes serious eye irritation (H319)

Toxic to aquatic life. (H401)

Precautionary Statements

Prevention: Wash hands thoroughly after handling. (P264)

Wear protective gloves/eye protection/face protection (P280)

Avoid release to the environment. (P273)

Response: IF ON SKIN: Wash with plenty of water. (P302 + P352) If skin irritation occurs: Get

medical advice/attention. (P332 + P313) Take off contaminated clothing and wash it

before reuse. (P362 + P354)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. (P305 + P351 + P338) If eye irritation

persists: Get medical advice/attention. (P337 + P313)

Storage: None required.

Dispose of in accordance with local, state and federal regulations. (P501) See

SECTION 13 - DISPOSAL CONSIDERATIONS, for additional waste disposal

information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical characterization:</u> Mixture (water based)

Ingredient:CAS NumberPercentProprietary surfactant blend *Proprietary5 - 10

* Composition of this ingredient is a trade secret.

4. FIRST AID MEASURES

Protection of First-Aiders: First aid responders should pay attention to self-protection and use the recommended

protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to SECTION 8 – EXPOSURE CONTROLS / PERSONAL

PROTECTION, for specific personal protective equipment.

Inhalation: No adverse effects are anticipated. Remove to fresh air. If breathing is difficult, get

medical assistance.

Eye contact: May cause serious eye damage. Immediately rinse with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately seek

medical attention.

Ingestion: No adverse health effects are anticipated. If swallowed, treat symptomatically and

supportively. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. If adverse health effects develop, persist or are severe, seek medical attention if you feel unwell. Never give anything by mouth to an unconscious

person.

Skin contact: Prolonged or repeated exposure may cause skin irritation. If on skin, wash with plenty

of water. If you feel unwell or irritation develops or persists, get medical attention. Take

off contaminated clothing and wash it before reuse.

Symptoms and effects, both acute

and delayed:

Aside from the information provided above and below, no additional symptoms and

effects are anticipated.

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of

symptoms and the clinical condition of the patient. Skin contact may aggravate pre-

existing dermatitis.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire

extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be

less effective. Do not use direct water stream. May spread fire.

Unusual fire and explosion hazards: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition

products:

Decomposition products may include the following materials; carbon dioxide, carbon

monoxide, nitrogen oxides.

Special precautions for fire fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving personal risk or without suitable

training

Special protective equipment for

fire fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Mirachem Ultrasonic XL Revision Date: 2017/10/24
Formula Number 2104 Page 2 of 7

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency

procedures:

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard. Use appropriate safety equipment. For additional information, refer to SECTION 8 - EXPOSURE CONTROLS AND

PERSONAL PROTECTION. Refer to SECTION 7 - HANDLING AND STORAGE, for

additional precautionary measures.

Environmental precautions: Prevent from entering into soil, ditches, storm sewers, waterways and/or ground water.

See SECTION 12 – ECOLOGICAL INFORMATION for additional information.

Methods for cleaning up: Contain spilled material; keep from entering soil, surface waters or sewers.

Small Spills: Clean up with absorbent and collect absorbent for disposal in accordance

with Federal, State or local disposal requirements.

Large Spills: Dike or otherwise contain spilled material to insure runoff does not reach a waterway. Collect and drum off material for disposal in accordance with Federal, State or local disposal requirements. Notify local, state or federal authorities if required. Rinse with water. See SECTION 13 – DISPOSAL CONSIDERATIONS and SECTION 15 –

REGULATORY REQUIREMENTS for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin and eyes. Avoid breathing spray or mist. Wash hands

thoroughly after handling. Keep container closed. Promptly clean up spills. See SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION for additional

information.

Conditions for safe storage, including incompatibilities:

Keep containers tightly closed. Protect from freezing; may rupture or degrade product.

Store between 40°F (4°C) and 110°F (43°C). Keep out of reach of children.

The shelf life for unopened containers stored under the above conditions is 36 months

from the date on the package.

Recommended packaging

materials:

Use original container or clean plastic (polyethylene) containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters: None established (under ACGIH or OSHA.)

Engineering controls: Good ventilation should be sufficient to control worker exposure to airborne

contaminants. Provide additional ventilation as necessary to keep airborne

concentrations of vapors/mists below threshold limit values. Provide eye wash station

within close proximity to product usage.

Eye/Face protection: Safety glasses with side shields (or chemical goggles) and face shield (if splashing is

likely) to prevent eye and face exposure.

Skin protection: Wear protective gloves/protective clothing as needed to prevent excessive skin contact.

Where diluted product is heated to >140°F, wear thermal protective gloves.

Hand protection: Wear chemical (alkali) resistant, impermeable gloves (nitrile, vinyl or latex of 4 mil

thickness or greater) as needed to prevent skin contact. Where diluted product is

heated to >140°F, wear thermal protective gloves.

Respiratory protection: Under intended handling conditions, no respiratory protection is needed.

Personal hygiene: Use good personal hygiene. Do not consume or store food in the work area. Wash

hands before smoking or eating.

Mirachem Ultrasonic XL
Formula Number 2104

Revision Date: 2017/10/24
Page 3 of 7

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Water white to light yellow

clear liquid

Odor: Mild detergent odor
Odor threshold: Not available
pH: 10.5 – 11.4
pH at use dilution (10%): 10.0 – 11.0

Melting point: Not applicable to liquids

Freezing point:

Initial boiling point:

Evaporation rate:

Flash point:

Flammability:

Flammable limits in air:

32°F (4°C)

212°F (100°C)

Not established

Not classified

Not established

Vapor pressure @ 20°C 0.0006 mm Hg* 0.0009 mm Hg* @ 37°C Vapor density (air = 1) Not established Relative density: Not established Solubility in water: Complete Partition coefficient: Not established Auto-ignition temperature: Not established **Decomposition temperature:** Not established Viscosity @ 20°C: < 100 cSt Liquid density @ 20°C: 1.04 g/cm³ VOC**, undiluted 75 g/l (0.6 lb./gal)

use dilution (10%) 75 g/l (0.06 lb./gal) 7.5 g/l (0.06 lb./gal)

* Absolute (calculated)

** The VOC in this product has a vapor pressure of less than 0.1 mm Hg. Under many jurisdictions, this is classified as a low vapor pressure VOC. This material is <u>not</u> listed as a "Hazardous Air Pollutant (HAP)" under the Clean Air Act (CAA) list of volatile or organic hazardous air pollutants.

10. STABILITY AND REACTIVITY

Chemical stability & reactivity: The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid: No specific data.

Incompatible materials: Avoid contact with strong acids, strong bases or strong oxidizers.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should

products: not be produced. Thermal decomposition may produce CO₂

11. TOXICOLOGICAL INFORMATION

The GHS health hazard classifications have been calculated adhering to GHS guidelines for mixtures. The Acute Toxicity Estimates for this mixture (ATE_{mix}) are representative of these calculations.

Likely routes of exposure:	Inhalation	Skin contact	X	Eye contact	X	Ingestion	
Likely foules of exposure.		Skill Colliact		Eye contact		ingestion	

Acute Toxicity:

Oral: Not classified LD_{50} ATE_{mix} > 2,500 mg/kg Dermal: LD_{50} ATE_{mix} > 2,500 mg/kg > 2,500 mg/kg

Inhalation: No relevant data available.

Other routes: Not applicable.

Skin corrosion/irritation: May be irritating to skin

Serious eye damage/irritation: May cause serious eye irritation

Skin sensitization: No component of this mixture is known to be a skin sensitizer.

Respiratory sensitizer: No relevant data available.

Chronic Toxicity:

Mutagenicity: No component in this mixture is known to be a mutagen or genotoxin.

Carcinogenicity: No component of this mixture is listed by IARC, NTP, OSHA or ACGIH as a

carcinogen.

Teratogenicity: No component in this mixture is known to be a teratogen.

Developmental / Fertility effects: No known significant effects or critical hazards.

Specific Target Organ Toxicity

Single dose:

No relevant data available.

Repeat exposure:

No relevant data available

Aspiration hazard: No relevant data available.

Mirachem Ultrasonic XL
Formula Number 2104

Revision Date: 2017/10/24
Page 4 of 7

12. ECOLOGICAL INFORMATION

The GHS health hazard classifications have been calculated adhering to GHS guidelines for mixtures. The Acute Toxicity Estimates for this mixture (ATE_{mix}) are representative of these calculations.

Toxicity:

Acute Aquatic Toxicity Fish Category 2 LC_{50} ATE_{mix} > 1 but < 10 mg/l Crustacea Category 3 EC_{50} ATE_{mix} > 10 but < 100 mg/l

Algae No relevant data available.

Chronic Aquatic Toxicity No relevant data available.

Persistence and degradability: The individual components of this mixture are readily biodegradable.

Bioaccumulative potential: No relevant data available. Mobility in soil: No relevant data available.

13. DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized wherever possible. Empty containers may retain some product residues. Rinse container before disposal. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff with soil and waterways.

RCRA Classification: Unused disposed material is *not* a RCRA Hazardous Waste.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, State and local waste disposal requirements may be more restrictive or otherwise different from Federal laws and regulations.

14. TRANSPORT INFORMATION

UN Number: UN 1760 Transportation Hazard Class: 8
UN Proper Shipping Name: Corrosive liquids, n.o.s. UN Packing Group: PG III

ADR (EU Carriage): Class 8: Corrosive, PG III RID (Rail) Class 8: Corrosive, PG III AND/ADNR (Inland water): Not available ICAO/IATA (Air) Class 8: Corrosive

IMO/IMDG (Marine): Class 8: Corrosive

DOT Shipping Name: UN 1760 Corrosive Liquid, n.o.s. (contains Alcohols, C₁₀-C₁₄, ethoxylated), 8, PG III

NMFC Freight Class: Cleaning Compound NOI, 48580, Sub 3, Class 55

HS Tariff Classification 3402.90.5030

(Schedule B)

Special Precautions: No known special precautions.

Mirachem Ultrasonic XL
Formula Number 2104

Revision Date: 2017/10/24
Page 5 of 7

15. REGULATORY INFORMATION

US Federal Regulations

SARA Title III

Substances

Section 302 - Extremely Hazardous Substance

This product does not contain chemicals at levels which require reporting under this statue.

Section 302.4 & 304: CERCLA: Hazardous

Releases of this product to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund

Amendments and Reauthorization Act (SARA) Title III Section 304.

Sections 311 & 312 Immediate (acute) Health Hazard

> Delayed (chronic) Health Hazard No Fire Hazard No Reactive Hazard No Sudden Release of Pressure No

Section 313 This product does not contain chemicals at levels which require reporting under this statue.

All chemical substances in this material are included on or exempted from listing on the TSCA **TSCA**

Inventory of Chemical Substances.

US State Regulations

Arizona Maricopa County Rule 331 This product is considered a Low-VOC cleaner.

California Safe Drinking Water This product does not contain any materials currently listed by California California and Toxic Enforcement Act as chemicals known to cause cancer or known to have reproductive

(Proposition 65) toxicity under Proposition 65.

R 336.1212

BAAQMD This product meets the requirements of the Bay Area Air Quality

Management District Regulation 8, Rule 16 when used at a 10% dilution with water. The VOC content at this dilution is 7.5 grams/Liter (0.06 pounds/gallon) with a composite partial pressure at 20°C of less than 1

Yes

mm Hg.

SCAQMD This product meets the requirements of South Coast Air Quality

Management District rules 1171 and 1122 when diluted with water to a 10% concentration. At this dilution, the VOC content is 7.5 g/L or 0.06 pounds/gallon with a composite partial pressure at 20°C of less than 1

mm Hg.

Georgia Rule 391-3-02 At use dilution, this product is greater than 80% water which qualifies this

as an "Aqueous Cleaning Solvent". As an "Aqueous Cleaning Solvent"

this product is exempt from Rule 391-3-02.

Michigan Rule R 336.1281 & The absolute (composite) vapor pressure of this product in either

concentrated or diluted form is less than 0.1 mm Hg under standard conditions. Part (e) under R 336.1281 exempts this product from the requirement for a "Permit to Install". The vapor pressure for this product exempts it from the recordkeeping requirements of R 366.1212 as indicated in Part (3)(b) and clarified by MDEQ interoffice communication

of July 5, 2011.

Pennsylvania Hazardous Substances List This product does not contain chemicals at levels which require reporting

under this statue.

Texas Rule 106.454 -**Texas** Under this rule, this product is classified as a zero VOC product. The true **Degreasing Units**

vapor pressure is calculated to be < 0.6 pounds per square inch,

absolute (psia) at an operating temperature of 100°F. This product meets the requirements of section (2)(C) for a remote reservoir cleaner and as such Section (1)(A) (i) and (ii) do not apply. Completion of Form PI-7 and

monthly record keeping is not required.

Mirachem Ultrasonic XL Revision Date: 2017/10/24 Formula Number 2104 Page 6 of 7

International Regulatory Information

Notice: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warrantee, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with their Federal, State/Province, and local laws. The following specific information is made for the purpose of complying with numerous specific foreign regulations.

Country Substance (Chemical) Inventories

Canada DSL The individual components of this mixture are listed.

United States TSCA All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical

Substances.

16. OTHER INFORMATION

HMIS Rating:



NFPA Rating:



Special

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Mirachem shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current status of scientific and technical knowledge.

Original Preparation Date: May 1, 2015 Latest Revision Date: October 24, 2017

Mirachem Ultrasonic XL
Formula Number 2104

Revision Date: 2017/10/24
Page 7 of 7